



PML 3RC PML 3FC PNEUMATIC FOOTSWITCH



PML 3RC - 4mm



PML 3FC - M5

GS Automation's PML 3RC / PML 3FC footswitch has anodized aluminum valve, connection Diam 4 (code PML 3RC) or connection M5 (code PML 3FC). Its housing is black Nylon with IP44 degree of protection. Double/Triple foot switches on Iron Plate all available features. The PML 3RC/PML 3FC pneumatic footswitch fulfills all relevant international standards for worldwide use in applications from all industries.

Main features

Material	Reinforced Nylon 30% Glass.
Color	Black(other colours on request)
Weight	0.200 Kg
Sizes	76 x 104 x 30 mm
Protection degree	IP44

Pneumatic valve

Type	Aluminum valve 3 ways
Connections	D4 – M5
PE	Up to 10 bar
Working temperature	-25 °C to +70 °C

Implementation

- Double and triple footswitches on iron plate.

Available Versions

Code	Description	Version	Connection
PF PML 3RC 00	Pneumatic Foot Switch	3 ways NO	connection Tube 4mm
PF PML 3RC 02	Pneumatic Foot Switch	3 ways NC	connection Tube 4mm
PF PML 3FC 00	Pneumatic Foot Switch	3 ways NO	connection M5
PF PML 3FC 02	Pneumatic Foot Switch	3 ways NC	connection M5



GS AUTOMATION

20099 SESTO SAN GIOVANNI – ITALY – VIA CARDUCCI 221/23-24 – PHONE: +39 02 240 8127
www.gs-automation.eu – email: gs@gs-automation.eu